


LAMP PHOTOMETRIC REPORT

MODEL: 95Livial60/GR		
POWER: 10W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 763.77 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	360.0	360.0	360.5	358.4	359.4	362.0	362.1	361.0	0- 10	34.73	34.73	4.55
20	337.2	336.9	336.4	334.0	338.0	338.4	339.5	338.6	10- 20	98.98	133.7	17.5
30	297.6	295.6	294.0	292.0	294.6	295.0	299.1	299.3	20- 30	146.6	280.3	36.7
40	239.3	236.7	233.9	230.0	231.1	234.7	240.8	242.7	30- 40	167.4	447.7	58.6
50	163.2	161.3	157.1	150.9	152.7	158.4	166.3	167.3	40- 50	153.6	601.4	78.7
60	77.25	74.55	73.43	69.24	72.44	75.96	81.04	79.90	50- 60	103.6	705.0	92.3
70	23.13	22.18	21.78	21.70	22.24	24.06	25.19	25.63	60- 70	45.74	750.7	98.3
80	3.127	2.954	2.971	3.027	3.226	3.365	3.544	3.498	70- 80	11.32	762.0	99.8
90	0.1729	0.1766	0.1854	0.1870	0.1459	0.1508	0.1581	0.1597	80- 90	1.737	763.8	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:19 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```